



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B



408-4022
17 DEC 09 Rev D
**Pressure Type Wire
Connector Combinations
Pre- Insulated Heat Sealable
Polyolefin Terminals and Splices** **CU**

TO BE SOLD ONLY
WITH INSTALLATION
INSTRUCTIONS

Shrink Temperature
149°C [300°F] (Min)

STRANDED WIRE		TOOL PART NUMBER
SIZE RANGE (AWG)	STRIP LENGTH mm [in.]	
22-18	7.94 [5/16]	55893-1
16-14	7.94 [5/16]	55893-1, 55894-1
12-10	9.52 [3/8]	55893-1, 55894-1
8	9.52 [3/8]	55894-1

©2009 Tyco Electronics Corporation, Harrisburg, PA
All International Rights Reserved.
TE logo and Tyco Electronics are trademarks.

TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
LOC B