



<b>Form Type</b>	Distribute	<b>Version</b>	2.0	<b>Ref</b>	IPC 1752A	<b>Sectionals</b>	Manufacturing Info/ Material Info	<b>Subsectionals</b>	D, A
<b>Supplier Information</b>									
<b>Company Name</b>	TE Connectivity	<b>Request Document ID</b>		<b>Contact Name</b>	Chan, Nelson	<b>Contact Title</b>	Manager Sales, HKG SELL DIR-EMS		
<b>Company Unique ID</b>	TE Connectivity	<b>Response Date</b>	2015-12-12	<b>Contact Email</b>	nelson.chan@te.com				
<b>Contact Phone Number</b>		+852-2738-8751							
<b>Legal Statement</b>									
<b>Supplier Acceptance</b>	true								
<b>Legal Statement</b>									
The information provided in this document is based upon reasonable inquiry of our suppliers. This information is subject to change. This information does not in any way modify existing purchase specifications or existing contractual or other agreements terms between TE Connectivity (or its affiliated companies) and its customers.									
<b>Product</b>									
<b>Manufacturer Item number</b>	747784-3	<b>Amount</b>	9401.41	<b>Version</b>	-	<b>Identity</b>			
<b>Manufacturer Item Name</b>	AMPLI JACKSCREW 4-40 KIT	<b>Weight Uom</b>	mg	<b>Mfr Site</b>		<b>Authority</b>			
<b>Date</b>		<b>UOM</b>	Each						
<b>EUROHS-0508</b>	Product(s) meets EU RoHS requirement without any exemptions								
<b>ChinaRoHS-0508</b>	Product(s) is eligible for marking with the e code under China's Measures for Administration of the control of pollution by Electronic Information Products								
<b>EUREACH-1214</b>	REACH Candidate Substances of Very High Concern ARE NOT Contained in the Product Above the Limits per the Definition within REACH								
<b>Manufacturing Information</b>									
<b>J-STD-020 MSL Rating</b>		<b>Max Total a Wave Time</b>		<b>Ramp Rate</b>		<b>Wave Additional Info</b>			
<b>Classification Temp</b>		<b>Max Wave Solder Time</b>	0.0	<b>Ramp Down Rate</b>		<b>Psl Rating Reflow</b>			
<b>Max Time Within 5</b>		<b>Psl Rating Wave</b>		<b>Package Designator</b>		<b>Size</b>	0.0		
<b>Time Above 217</b>		<b>Reflow Additional Info</b>		<b>Preheat Max Temp</b>		<b>Terminal Base Alloy</b>	NAC		
<b>Preheat Duration</b>		<b>bulk Solder Termination</b>	NAC	<b>Nbr or Reflow Cycles</b>		<b>Terminal Plating</b>	NAC		
<b>Preheat Min Temp</b>		<b>Nbr of Instances</b>	0	<b>Component Temp Spike</b>		<b>Shape</b>	NAC		
<b>Product Disclosure</b>									
<b>Sub-Item/Material/Substance</b>	<b>Level</b>	<b>Name</b>	<b>Substance Category</b>	<b>Substance CAS</b>	<b>Substance Concentration</b>	<b>Quantity</b>	<b>Mass per Unit</b>	<b>UOM</b>	<b>Exemption</b>
Sub-Item	1	JACKSCREW, MALE, STAINLESS STEEL				1.0	9401.41	mg	
Material	2	Stainless Steel				1.0	9401.41	mg	
Substance	3	Arsenic	Supplier	7440-38-2	0.01	1.0	0.94014	mg	
Substance	3	Carbon	Supplier	7440-44-0	0.15	1.0	14.10212	mg	
Substance	3	Sulfur	Supplier	7704-34-9	0.15	1.0	14.10212	mg	
Substance	3	Silicon	Supplier	7440-21-3	1.0	1.0	94.0141	mg	
Substance	3	Cobalt	Supplier	7440-48-4	0.1	1.0	9.40141	mg	
Substance	3	Phosphorus	Supplier	7723-14-0	0.06	1.0	5.64085	mg	
Substance	3	Manganese	Supplier	7439-96-5	1.25	1.0	117.51763	mg	
Substance	3	Antimony	Supplier	7440-36-0	0.01	1.0	0.94014	mg	
Substance	3	Iron	Supplier	7439-89-6	82.6585	1.0	7771.06448	mg	
Substance	3	Chromium	Supplier	7440-47-3	14.0	1.0	1316.1974	mg	
Substance	3	Beryllium	Supplier	7440-41-7	0.0010	1.0	0.0940141	mg	
Substance	3	Lead	Lead/Lead Compounds	7439-92-1	0.1	1.0	9.40141	mg	
Substance	3	Cadmium	Cadmium/Cadmium Compounds	7440-43-9	0.01	1.0	0.94014	mg	
Substance	3	Mercury	Mercury/Mercury Compounds	7439-97-6	5.0E-4	1.0	0.04700705	mg	
Substance	3	Nickel	Nickel	7440-02-0	0.5	1.0	47.00705	mg	