


- Notes
- 1 The recommended tightening torque of REF. No. ④ : 7 to 7.5 N·m.
Thread locker to the threaded portion of REF. No. ④ is recommended to prevent loosening.
The recommended thread locker : LOCTITE 243, HENKEL JAPAN CO, LTD.
 2. Rotation examples are shown for REF. No. ① and ④.
 3. The cable pull and twisting strength, waterproof tightness, and other characteristics may differ, depending on the cable structure, please confirm before the use.
 - 4 Panel cutout is an example to case of fixing mating side.
 5. Applicable mating connector : HR43-21WBP-3SC (CL143-0001-0).

4	Aluminum alloy	Chrome plating						
3	PBT	Black	7	PBT	Black			
2	Silicone rubber	Black	6	PBT	Black			
1	Aluminum alloy	Chrome plating	5	Silicone rubber	Black			
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS			
UNITS mm		SCALE 2 : 1		COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 HIROSE ELECTRIC CO., LTD.	APPROVED	・HY. KOBAYASHI	16. 04. 01	DRAWING NO.	EDC-117730-00-00			
	CHECKED	・HY. KOBAYASHI	16. 04. 01	PART NO.	HR43-21WBJ-3PC			
	DESIGNED	・TH. KAMEYA	16. 03. 31	CODE NO.	CL143-0002-2-00			
	DRAWN	・TH. KAMEYA	16. 03. 31	