



**Basic features**

<b>Approval/Conformity</b>	CE EAC cURus cULus WEEE
<b>Basic standard</b>	EN 61204
<b>Series</b>	Standard
<b>Short description</b>	Switching power supply
<b>Version</b>	DIN rail

**Electrical connection**

<b>Connection</b>	0.25...4 mm <sup>2</sup>
<b>Interconnected operation type</b>	Parallel wiring: max. 3 devices Series wiring: max. 2 devices
<b>Short-circuit protection</b>	pulsed / Forward characteristic

**Electrical data**

<b>Derating</b>	-2.5 %/°C +61 °C
<b>Efficiency typ.</b>	91 %
<b>Hold-up time</b>	≥ 20 ms at 400 V AC
<b>Input fuse</b>	T 3.15 A (3x)
<b>Input voltage</b>	400...500 V AC 3-phase
<b>Input voltage</b>	340...575 V AC 480...820 V DC
<b>Input/output insulation voltage</b>	3000 V AC
<b>Inrush current</b>	≤ 25 A at 400 V AC
<b>Isolation resistance</b>	≥ 100 MOhm
<b>Load control</b>	±5 % parallel ±1 % single
<b>Output power max.</b>	480 W
<b>Output voltage</b>	24 VDC
<b>Output voltage, tolerance</b>	+1 %
<b>Protection class</b>	I
<b>Rated input current</b>	1.1 A at 400 V AC
<b>Rated output current</b>	20 A
<b>Residual ripple max.</b>	100 mV
<b>Setting range</b>	24...28 V DC
<b>Settling time</b>	2 ms
<b>Switching frequency</b>	80000 Hz

Switching Power Supplies  
**BAE PS-XA-3Y-24-200-022**  
Order Code: BAE0117

**BALLUFF**

Turn-on time max.	1 s
Voltage control	1 %
Working frequency	47...63 Hz

**Environmental conditions**

Ambient temperature	-25...80 °C
Contamination scale	2
Cooling	Free convection
EN 60068-2-27, Shock	15 g, 11 ms, xyz-axis, 6 surfaces (3x)
EN 60068-2-6, Vibration	2 g, 10...500 Hz, xyz-axis, 60 min
Over temperature	protected
Protection degree	IP20
Relative humidity	20...95 %, non-condensing
Storage temperature	-25...85 °C
Temperature coefficient max.	±0.03 %/K

**Functional safety**

MTTF (40 °C)	47 a
--------------	------

**Material**

Housing material	Metal
------------------	-------

**Mechanical data**

Dimension	140 x 121 x 117.3 mm
Mounting	DIN rail mount
Weight	1.35 kg

**Remarks**

Values measured at +25 °C and full load.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Wiring Diagrams**

