



4MT5
(CYJV CABLE ASSEMBLY)



Basic features

| | |
|---------------------|----------------------------|
| Approval/Conformity | CE cULus EAC WEEE |
|---------------------|----------------------------|

Electrical connection

| | |
|-------------------------------------|--|
| Bending radius min., fixed cable | 5 x D |
| Bending radius min., flexible cable | 10 x D |
| Cable | PUR black, 10 m, Drag chain compatible |
| Cable diameter D | 4.70 mm ±0.20 mm |
| Cable, bending cycles min. | 5 million |
| Conductor cross-section | 0.34 mm ² |
| Connection | M8x1-Female, straight, 4-pin, A-coded |
| Connector configuration | Straight |
| Number of conductors | 4 |
| Number of pins | 4 |
| System | Molded |

Electrical data

| | |
|-------------------------|-----------------|
| Operating voltage U_b | 60 VDC / 60 VAC |
| Rated current (40 °C) | 4.0 A |

Environmental conditions

| | |
|---|-------------|
| Cable temperature UL max., fixed routing | 80 °C |
| Cable temperature UL max., flexible routing | 80 °C |
| Cable temperature, drag chain | -25...60 °C |
| Cable temperature, fixed routing | -50...90 °C |
| Cable temperature, flexible routing | -25...90 °C |
| Protection degree | IP67, IP69K |

Material

| | |
|--------------------------|--------------------------------------|
| Cable jacket, material | PUR |
| Material contact carrier | PUR |
| Material contacts | Bronze |
| Material cover nut | Die-cast zinc or nickel plated brass |
| Material grip | PUR |

Mechanical data

| | |
|---|-----------------------|
| Acceleration max., drag chain | 5 m/s ² |
| Cable jacket, color | black |
| Cable length L | 10.00 m |
| Cable properties | Drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m |
| Tightening torque pigtail | 0.4 Nm |
| Traverse speed max., drag chain | 200 m/min |
| Vertical travel permitted, drag chain | 5 m |

Output/Interface

| | |
|------------------|---------------|
| Switching output | Complementary |
|------------------|---------------|

Remarks

Cable construction acc. to UL-AWM Style 20549
Halogen-free per DIN VDE 0472 Part 815
Silicone-free
Flame-retarding acc. to IEC 60332-2
Enclosure rating per IEC 60529 or 20653, only in screwed state with the associated mating piece.

Connector Drawings



PIN 1: brown
PIN 2: white
PIN 3: blue
PIN 4: black

Wiring Diagrams

