



Basic features

Approval/Conformity	CE EAC cULus WEEE
---------------------	----------------------------

Electrical connection

Cable diameter D	3.00 mm
Cable length L	2 m
Connection type	Cable, 2.00 m, PUR
Number of conductors	3

Electrical data

No-load current I ₀ max., damped	2 mA
No-load current I ₀ max., undamped	7 mA
Operating voltage U _b	10...30 VDC
Output resistance R _a	33.0 kOhm
Protection class	II
Rated insulation voltage U _i	250 V AC
Ready delay t _v max.	25 ms
Residual current I _r max.	10 µA
Ripple max. (% of U _e)	10 %
Switching frequency	5000 Hz

Environmental conditions

Ambient temperature	-25...70 °C
Protection degree	IP68

Functional safety

MTTF (40 °C)	595 a
--------------	-------

Material

Housing material	Brass, Nickel-free coated
Material jacket	PUR
Material sensing surface	PBT
Surface protection	Nickel-free coated

Mechanical data

Dimension	Ø 8 x 50 mm
Installation	for flush mounting
Size	M8x1

Output/Interface

Switching output	PNP normally closed (NC)
------------------	--------------------------

Range/Distance

Assured operating distance S _a	1.2 mm
Rated operating distance S _n	1.5 mm
Real switching distance s _r	1.5 mm
Switching distance marking	■

Wiring Diagrams

