


1) Optical axis, 2) Output function, 3) stability/error, 4) Sn



### Basic features

<b>Approval/Conformity</b>	CE cULus EAC WEEE
<b>Basic standard</b>	IEC 60947-5-2
<b>Principle of operation</b>	Photoelectric sensor
<b>Series</b>	18KF
<b>Style</b>	Flat cylinder Straight optics
<b>Trademark</b>	Global

### Display/Operation

<b>Adjuster</b>	button
<b>Display</b>	Output function- LED yellow Error - LED green, flashing Stability - LED green
<b>Setting</b>	Rated switching distance (Sn)

### Electrical connection

<b>Cable diameter D</b>	4.00 mm
<b>Cable length L</b>	2 m
<b>Conductor cross-section</b>	0.14 mm <sup>2</sup>
<b>Connection</b>	Cable, 2.00 m, PVC
<b>Number of conductors</b>	4
<b>Polarity reversal protected</b>	yes
<b>Short-circuit protection</b>	yes

### Electrical data

<b>No-load current I<sub>o</sub> max. at U<sub>e</sub></b>	30 mA
<b>Operating voltage U<sub>b</sub></b>	10...30 VDC
<b>Rated insulation voltage U<sub>i</sub></b>	75 V DC
<b>Rated operating current I<sub>e</sub></b>	100 mA
<b>Rated operating voltage U<sub>e</sub> DC</b>	24 V
<b>Ripple max. (% of U<sub>e</sub>)</b>	8 %
<b>Switching frequency</b>	500 Hz
<b>Turn-off delay t<sub>off</sub> max.</b>	1 ms
<b>Turn-on delay t<sub>on</sub> max.</b>	1 ms
<b>Voltage drop U<sub>d</sub> max. at I<sub>e</sub></b>	2 V

Photoelectric Sensors  
**BOS 18KF-NA-1HA-C-02**  
 Order Code: BOS00HP

**BALLUFF**

**Environmental conditions**

Ambient temperature	-25...55 °C
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms, 3x6
EN 60068-2-6, Vibration	10...55 Hz, amplitude 0.5 mm, 3x30 min
Protection degree	IP67

**Functional safety**

MTTF (40 °C)	700 a
--------------	-------

**Material**

Housing material	PBT
Material jacket	PVC
Material sensing surface	PMMA

**Mechanical data**

Dimension	Ø 18 x 91.5 mm
Mounting	Nut M18x1 Screw M3
Tightening torque max.	1.5 Nm

**Optical features**

Ambient light max.	5000 Lux
Light spot size	Ø 8 mm at 100 mm
Light type	LED, red light
Principle of optical operation	Diffuse sensor, triangulation
Special optical feature	Background suppression
Switching function, optical	Light/dark switching
Wave length	630 nm

**Output/Interface**

Switching output	NPN normally open (NO) NPN NC Pins 4-2
------------------	---

**Range/Distance**


Range	50...100 mm
Rated operating distance Sn	100 mm Adjustable

**Remarks**

The sensor is functional again after the overload has been eliminated.  
 For additional information, refer to user's guide.  
 Order accessories separately.  
 Do not press key using a pointed tool.  
 Reference object (target): gray card, 100 x 100, 90 % remission, axial approach.  
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Wiring Diagrams**



**Opto Symbols**

