


1) Alignment mode active, 2) Power/alignment mode active, 3) Alignment mode on/off, 4) Optical axis, 5) rotatable 270°



Basic features

Approval/Conformity	CE cULus Ecolab EAC WEEE
Basic standard	IEC 60947-5-2
Principle of operation	Photoelectric sensor
Reference receiver	BOS 23K-GI-RE10-S4
Series	23K
Style	Square Connection can be rotated

Electrical connection

Connection	Connector, M12x1-Male, 4-pin
Polarity reversal protected	yes
Protection against device mix-ups	yes

Electrical data

Input function	Test (Emitter off)
No-load current I_{o max.} at U_e	30 mA
Operating voltage U_b	18...30 VDC
Rated operating voltage U_{e DC}	24 V
Ripple max. (% of U_e)	10 %

Display/Operation

Adjuster	button
Display	Setup mode - LED yellow+green, alt. LED green: Power
Setting	Alignment mode on/off

Environmental conditions

Ambient temperature	-20...60 °C
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms, 3x6
EN 60068-2-6, Vibration	10...55 Hz, amplitude 0.5 mm, 3x30 min
IP rating per DIN 40050	IPx9K
Protection degree	IP6x

Functional safety

MTTF (40 °C) 494 a

Material

Housing material PC
 ABS
 Material sensing surface PMMA

Mechanical data

Dimension 23 x 51 x 52.4 mm
 Mounting Screw M4
 Tightening torque max. 1.5 Nm

Optical features

Beam characteristic Divergent
 LED group per IEC 62471 Exempt Group
 Light spot size 600 x 600 mm at 20 m
 Light type LED, red light
 Principle of optical operation Through-beam sensor (Emitter)
 Wave length 640 nm

Output/Interface

Baud rate 38.4 kBaud
 Interface IO-Link
 Process data cycle min. 5 ms

Range/Distance

Range 0...20 m
 Rated operating distance Sn 20 m Adjustable

Remarks


Do not press key using a pointed tool.
 Order accessories separately.
 For additional information, refer to user's guide.
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams



Opto Symbols

