





408-2049-29
28 JAN 11 Rev E
CU

**PLASTI-GRIP® Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND® Connectors)**

TO BE SOLD
ONLY WITH
INSTALLATION
INSTRUCTIONS

UL and CSA Wire Combinations

	Recognized Under the Component Program of UL File E13288		LR 7189 CERTIFIED
			8-2/0 AWG Stranded Wire
600 Volts Max	8-2/0 AWG Stranded Wire	8-2/0 AWG Solid or Stranded Wire	

105 °C [222 °F] Max

NOTE: Only certain terminal part numbers apply.

©2011 Tyco Electronics Corporation, Berwyn, PA
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
*Trademark. TE logo and Tyco Electronics are trademarks. visit our website at www.tycoelectronics.com

LOC B





408-2049-29
28 JAN 11 Rev E
CU

**PLASTI-GRIP® Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND® Connectors)**

TO BE SOLD
ONLY WITH
INSTALLATION
INSTRUCTIONS

UL and CSA Wire Combinations

	Recognized Under the Component Program of UL File E13288		LR 7189 CERTIFIED
			8-2/0 AWG Stranded Wire
600 Volts Max	8-2/0 AWG Stranded Wire	8-2/0 AWG Solid or Stranded Wire	

105 °C [222 °F] Max

NOTE: Only certain terminal part numbers apply.

©2011 Tyco Electronics Corporation, Berwyn, PA
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
*Trademark. TE logo and Tyco Electronics are trademarks. visit our website at www.tycoelectronics.com

LOC B





408-2049-29
28 JAN 11 Rev E
CU

**PLASTI-GRIP® Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND® Connectors)**

TO BE SOLD
ONLY WITH
INSTALLATION
INSTRUCTIONS

UL and CSA Wire Combinations

	Recognized Under the Component Program of UL File E13288		LR 7189 CERTIFIED
			8-2/0 AWG Stranded Wire
600 Volts Max	8-2/0 AWG Stranded Wire	8-2/0 AWG Solid or Stranded Wire	

105 °C [222 °F] Max

NOTE: Only certain terminal part numbers apply.

©2011 Tyco Electronics Corporation, Berwyn, PA
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
*Trademark. TE logo and Tyco Electronics are trademarks. visit our website at www.tycoelectronics.com

LOC B





408-2049-29
28 JAN 11 Rev E
CU

**PLASTI-GRIP® Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND® Connectors)**

TO BE SOLD
ONLY WITH
INSTALLATION
INSTRUCTIONS

UL and CSA Wire Combinations

	Recognized Under the Component Program of UL File E13288		LR 7189 CERTIFIED
			8-2/0 AWG Stranded Wire
600 Volts Max	8-2/0 AWG Stranded Wire	8-2/0 AWG Solid or Stranded Wire	

105 °C [222 °F] Max

NOTE: Only certain terminal part numbers apply.

©2011 Tyco Electronics Corporation, Berwyn, PA
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
*Trademark. TE logo and Tyco Electronics are trademarks. visit our website at www.tycoelectronics.com

LOC B





408-2049-29
28 JAN 11 Rev E
CU

**PLASTI-GRIP® Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND® Connectors)**

TO BE SOLD
ONLY WITH
INSTALLATION
INSTRUCTIONS

UL and CSA Wire Combinations

	Recognized Under the Component Program of UL File E13288		LR 7189 CERTIFIED
			8-2/0 AWG Stranded Wire
600 Volts Max	8-2/0 AWG Stranded Wire	8-2/0 AWG Solid or Stranded Wire	

105 °C [222 °F] Max

NOTE: Only certain terminal part numbers apply.

©2011 Tyco Electronics Corporation, Berwyn, PA
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
*Trademark. TE logo and Tyco Electronics are trademarks. visit our website at www.tycoelectronics.com

LOC B





408-2049-29
28 JAN 11 Rev E
CU

**PLASTI-GRIP® Pressure Type
Straight and 90-Degree Bent
Terminals (Use Tooling for
AMPLI-BOND® Connectors)**

TO BE SOLD
ONLY WITH
INSTALLATION
INSTRUCTIONS

UL and CSA Wire Combinations

	Recognized Under the Component Program of UL File E13288		LR 7189 CERTIFIED
			8-2/0 AWG Stranded Wire
600 Volts Max	8-2/0 AWG Stranded Wire	8-2/0 AWG Solid or Stranded Wire	

105 °C [222 °F] Max

NOTE: Only certain terminal part numbers apply.

©2011 Tyco Electronics Corporation, Berwyn, PA
TOOLING ASSISTANCE CENTER 1-800-722-1111
PRODUCT INFORMATION 1-800-522-6752
*Trademark. TE logo and Tyco Electronics are trademarks. visit our website at www.tycoelectronics.com

LOC B