



1) O-Ring with thrust ring



Basic features

Approval/Conformity	CE UKCA WEEE
Basic standard	IEC 60947-5-2

Display/Operation

Function indicator	no
Power indicator	no

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Load capacitance max. at U_e	1 μ F
Min. operating current I_m	0 mA
No-load current I_o max., damped	25 mA
No-load current I_o max., undamped	12 mA
Operating voltage U_b	10...30 VDC
Output resistance R_a	2.0 kOhm + D
Rated insulation voltage U_i	75 V DC
Rated operating current I_e	130 mA
Rated operating voltage U_e DC	24 V
Rated short circuit current	100 A
Ready delay t_v max.	10 ms
Residual current I_r max.	80 μ A
Ripple max. (% of U_e)	15 %
Switching frequency	400 Hz
Utilization category	DC -13
Voltage drop static max.	3.5 V

Environmental conditions

Ambient temperature	-25...80 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 g_n , 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP68

Functional safety

MTTF (40 °C)	1620 a
--------------	--------

Inductive Sensors
BES 516-300-S190-S4
Order Code: BHS0026



Interface

Switching output PNP normally open (NO)

Material

Gasket, material NBR 60-80
Housing material Stainless steel
Material sensing surface PEEK
Support ring material PTFE

Mechanical data

Dimension $\varnothing 18 \times 58$ mm
Installation for flush mounting
Mounting part M18x1
Pressure rating max. 500 bar
Pressure rating, note oil pressure rated
Sealing ring, size 13×1.5 mm
Size M18x1
Tightening torque 40 Nm ± 10 %

Range/Distance

Assured operating distance Sa 2.1 mm
Hysteresis H max. (% of Sr) 15.0 %
Rated operating distance Sn 3 mm
Real switching distance sr 3 mm
Repeat accuracy max. (% of Sr) 5.0 %
Temperature drift max. (% of Sr) 10 %
Tolerance Sr -20 %

Remarks

Installation Guide 836665

The sensor is functional again after the overload has been eliminated.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

