



1) Sensing surface



Basic features

Application	Optimized response path especially suited for short-stroke cylinders.
Approval/Conformity	cULus CE UKCA WEEE
Basic standard	IEC 60947-5-2
Not incl. in scope of delivery	Mounting bracket, e.g. BMF 103-HW-42
Principle of operation	Magnetic field sensor

Display/Operation

Function indicator	yes
---------------------------	-----

Electrical connection

Cable	PUR, 2 m
Cable diameter D	2.50 mm
Conductor cross-section	0.10 mm ²
Number of conductors	3
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

Electrical data

Assured switching field strength Ha	2 kA/m
Hysteresis H max. (% of Hn)	45 %
Load capacitance max. at Ue	1 µF
No-load current Io max., undamped	3.5 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	Open drain
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	100 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Rated switch field strength Hn	1.2 kA/m
Residual current Ir max.	10 µA
Ripple max. (% of Ue)	15 %
Switching frequency	30000 Hz
Turn-off delay toff max.	0.02 ms
Turn-on delay ton max.	0.02 ms
Utilization category	DC -13
Voltage drop static max.	1 V

Environmental conditions

Ambient temperature	-25...85 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
ESD	2A (4 kV)
Emission	Group 1, Class B
IP rating	IP67

Magnetic Sensors
BMF 103K-PS-C-2A-PU-02
Order Code: **BMF001E**

BALLUFF

Functional safety

MTTF (40 °C) 739 a

Interface

Switching output PNP normally open (NO)

Material

Housing material PBT
Material jacket PUR
Material sensing surface PBT

Mechanical data

Dimension 9 x 4.8 x 16 mm
Mounting part Mounting bracket BMF 103-HW*

Remarks

The sensor is functional again after the overload has been eliminated.

Switching frequency f_{max} : Measured at 50 % duty cycle and 20 % I_e

UL-MARKINGS: - For use in NFPA 79 Applications only - Adapters providing field wiring means are available from the manufacturer. Refer to manufacturers information.

For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Wiring Diagrams

