



Basic features

| | |
|---------------------|---------------------|
| Approval/Conformity | CE cULus WEEE |
|---------------------|---------------------|

Electrical connection

| | |
|-------------------------------------|--|
| Bending radius min., fixed cable | 5 x D |
| Bending radius min., flexible cable | 10 x D |
| Cable | PVC Shielded gray, 15 m, drag chain compatible |
| Cable diameter D | 5.40 mm ±0.10 mm |
| Cable, bending cycles min. | 2 mil. |
| Conductor cross-section | 0.34 mm ² |
| Connection | M12x1-Female, straight, 5-pin, A-coded |
| Connector configuration | Straight |
| Number of conductors | 4 |
| Number of pins | 5 |
| System | Molded |

Electrical data

| | |
|-------------------------|-------------------|
| Operating voltage U_b | 250 VDC / 250 VAC |
| Rated current (40 °C) | 4.0 A |

Environmental conditions

| | |
|-------------------------------------|--------------|
| Cable temperature, drag chain | -5...60 °C |
| Cable temperature, fixed routing | -40...105 °C |
| Cable temperature, flexible routing | -5...105 °C |
| IP rating | IP67 |

Interface

| | |
|------------------|---------------|
| Switching output | Complementary |
|------------------|---------------|

Material

| | |
|-----------------------------|--------------------------|
| Cable jacket material, note | Shielded |
| Cable jacket, material | PVC |
| Cable shield | Copper braid, tin-plated |
| Material contact carrier | PUR |
| Material contacts | Bronze |
| Material cover nut | Brass nickel-plated |
| Material grip | PUR |


Mechanical data

| | |
|---|-----------------------|
| Acceleration max., drag chain | 5 m/s ² |
| Cable jacket, color | gray |
| Cable length L | 15.00 m |
| Cable properties | drag chain compatible |
| Horizontal travel permitted, drag chain | 5 m |
| Tightening torque pigtail | 0.6 Nm |
| Traverse speed max., drag chain | 200 m/min |
| Vertical travel permitted, drag chain | 2 m |

Remarks


Cable construction acc. to UL-AWM Style 2517
Silicone-free
Flame resistance acc. to FT1
Enclosure rating per IEC 60529, only in screwed state with the associated mating piece.

Connector Drawings



PIN 1: brown
PIN 2: white
PIN 3: blue
PIN 4: black

Wiring Diagrams



1) Shield on cover nut