



1) Sensing surface



### Basic features

Approval/Conformity	CE UKCA cULus WEEE
Base type deviation	PIGTAIL M12 / 0.3M
Basic standard	IEC 60947-5-2

### Display/Operation

Function indicator	yes
Power indicator	no

### Electrical connection

Cable diameter D	3.00 mm
Cable length L	0.3 m
Connection	M12x1-Male, 4-pin, A-coded
Connection type	Cable with connector, 0.30 m, PUR
Polarity reversal protected	yes
Protection against device mix-ups	yes
Short-circuit protection	yes

### Electrical data

Load capacitance max. at Ue	0.2 µF
Min. operating current Im	1 mA
No-load current Io max., damped	10 mA
No-load current Io max., undamped	3 mA
Operating voltage Ub	10...30 VDC
Output resistance Ra	Open collector
Rated insulation voltage Ui	75 V DC
Rated operating current Ie	100 mA
Rated operating voltage Ue DC	24 V
Rated short circuit current	100 A
Ready delay tv max.	15 ms
Residual current Ir max.	10 µA
Ripple max. (% of Ue)	10 %
Switching frequency	3000 Hz
Utilization category	DC -13
Voltage drop static max.	2.5 V

### Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
IP rating	IP67

### Functional safety

MTTF (40 °C)	830 a
--------------	-------

Inductive Sensors  
**BES 516-3040-I02-C-S4-00,3**  
Order Code: BES019T

**BALLUFF**

**Interface**

Switching output PNP normally open (NO)

**Material**

Housing material Aluminium, Anodized  
Material jacket PUR  
Material sensing surface PBT

**Range/Distance**

Assured operating distance Sa 0.65 mm  
Hysteresis H max. (% of Sr) 15.0 %  
Rated operating distance Sn 0.8 mm  
Real switching distance sr 0.8 mm  
Repeat accuracy max. (% of Sr) 5.0 %  
Temperature drift max. (% of Sr) 20 %  
Tolerance Sr ±10 %

**Mechanical data**

Dimension 25 x 5 x 5 mm  
Installation for flush mounting  
Size 5x5

**Remarks**

ESD requirements met if housing is grounded.  
EMC: For operating conditions with noise sources  
External protection circuit is required. Document 825345.  
The sensor is functional again after the overload has been eliminated.  
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

**Connector Drawings**



**Wiring Diagrams**

