



1) Sensing surface



Basic features

| | |
|----------------------------|---------------|
| Approval/Conformity | CE |
| | UKCA |
| | cULus |
| | WEEE |
| Basic standard | IEC 60947-5-2 |

Display/Operation

| | |
|---------------------------|-----|
| Function indicator | yes |
| Power indicator | no |

Electrical connection

| | |
|--|------------------|
| Connection | M8x1-Male, 3-pin |
| Polarity reversal protected | yes |
| Protection against device mix-ups | yes |
| Short-circuit protection | yes |

Electrical data

| | |
|---|---------------|
| Load capacitance max. at Ue | 0.5 μ F |
| Min. operating current I_m | 0 mA |
| No-load current I_o max., damped | 12 mA |
| No-load current I_o max., undamped | 4 mA |
| Operating voltage U_b | 10...30 VDC |
| Output resistance R_a | 33.0 kOhm + D |
| Rated insulation voltage U_i | 75 V DC |
| Rated operating current I_e | 200 mA |
| Rated operating voltage U_e DC | 24 V |
| Rated short circuit current | 100 A |
| Ready delay t_v max. | 10 ms |
| Residual current I_r max. | 80 μ A |
| Ripple max. (% of U_e) | 15 % |
| Switching frequency | 2000 Hz |
| Utilization category | DC -13 |
| Voltage drop static max. | 2.5 V |

Environmental conditions

| | |
|--------------------------------|---------------------------------------|
| Ambient temperature | 0...70 °C |
| Contamination scale | 3 |
| EN 60068-2-27, Shock | Half-sinus, 30 g _n , 11 ms |
| EN 60068-2-6, Vibration | 55 Hz, amplitude 1 mm, 3x30 min |
| IP rating | IP67 |

Functional safety

| | |
|---------------------|-------|
| MTTF (40 °C) | 830 a |
|---------------------|-------|

Inductive Sensors
BES Q08ZE-PSC25B-S49G
Order Code: BES01UY



Interface

Switching output PNP normally open (NO)

Material

Housing material Zinc, Die casting
 Material sensing surface PBT

Mechanical data

Dimension 59 x 8 x 8 mm
 Installation for flush mounting
 Size 8x8

Range/Distance

Assured operating distance Sa 2 mm
 Hysteresis H max. (% of Sr) 20.0 %
 Rated operating distance Sn 2.5 mm
 Real switching distance sr 2.5 mm
 Repeat accuracy max. (% of Sr) 5.0 %
 Switching distance marking ■■
 Temperature drift max. (% of Sr) 10 %
 Tolerance Sr ±10 %

Remarks

The sensor is functional again after the overload has been eliminated.
 Installation Instructions 850741
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings



Wiring Diagrams

