



1) Reference edge, 2) Sensing surface, 3) Sealing ring, 4) Function indicator FD/FE/LL



**Basic features**

<b>Approval/Conformity</b>	CE UKCA WEEE
<b>Basic standard</b>	IEC 60947-5-2
<b>Operating principle</b>	1-4. Switch position: Inductive
<b>Version</b>	Inductive

**Display/Operation**

<b>Function indicator</b>	1-4. Switch position: Optical fiber
---------------------------	-------------------------------------

**Electrical connection**

<b>Connection type</b>	1-4. Switch position: Screw terminal
<b>Electrical version</b>	3-/4-wire

**Electrical data**

<b>Continuous current</b>	1-4. Switch position: 0.13 A
<b>Rated operating voltage Ue</b>	1-4. Switch position: 24 V DC

**Environmental conditions**

<b>Ambient temperature</b>	-25...70 °C
<b>IP rating</b>	IP67

**Functional safety**

<b>MTTF (40 °C)</b>	BES 517-312-Y: 1620 a
---------------------	-----------------------

**Interface**

<b>Switching output</b>	PNP normally open (NO)
-------------------------	------------------------

**Material**

<b>Housing material</b>	Aluminium, Anodized
<b>Housing material, surface protection</b>	Anodized

**Mechanical data**

<b>Dimension</b>	72 x 64 x 59.5 mm
<b>Distance cam - active surface</b>	1-4. Switch position: 0...0.90 mm
<b>Flange, feed-through</b>	1 threaded exit M16
<b>Installation</b>	Vertical
<b>Plunger spacing 1st switch position</b>	26 mm
<b>Switching element</b>	1-4. Switch position: BES 517-312-Y

**Range/Distance**

<b>Assured operating distance Sa</b>	1-4. Switch position: 0.9 mm
<b>Range</b>	1.1 mm
<b>Rated operating distance Sn</b>	1-4. Switch position: 1.1 mm
<b>Switch position spacing</b>	8 mm

## Wiring Diagrams

